

**ATTACHMENT E: POST-INJECTION SITE CARE AND SITE CLOSURE PLAN
40 CFR 146.93(a)**

Elk Hills A1-A2 Storage Project

Facility Information

Facility Name: Elk Hills A1-A2 Storage Project
357-7R & 355-7R

Facility Contact: Travis Hurst / CCS Project Manager
28590 Highway 119

Tupman, CA 93276
(661) 342-2409 / Travis.Hurst@crc.com

Well Location: Elk Hills Oil Field, Kern County, CA
35.32802963 / -119.5449982

This Post-Injection Site Care and Site Closure (PISC) plan describes the activities that Carbon TerraVault I LLC (CTV) will perform to meet the requirements of 40 CFR 146.93. CTV will monitor ground water quality and track the position of the carbon dioxide plume and pressure front for 50 years post injection. CTV will not cease post-injection monitoring until a demonstration of non-endangerment of USDWs has been approved by the UIC Program Director pursuant to 40 CFR 146.93(b)(3). Following approval for site closure, CTV will plug all monitoring wells, restore the site to its original condition, and submit a site closure report and associated documentation.

Pre- and Post-Injection Pressure Differential [40 CFR 146.93(a)(2)(i)]

Based on the modeling of the pressure front as part of the AoR delineation, pressure at the injection well is expected to stabilize within one year after injection ceases. Injection limits will be based on the fracture pressure of the Monterey Formation A1-A2 and final pressure post injection will target the initial reservoir pressure at the time of discovery. Additional information on the projected post-injection pressure declines and differentials is presented in the permit application, and the AoR and Corrective Action Plan.


Discussion

The Monterey Formation A1-A2 reservoir will be operated such that the pressure will not exceed the initial pressure at the time of discovery. This operating strategy was developed to minimize the potential for induced seismicity and to ensure confinement of the injectate.

The maximum pressure differential between the injection wellbore and the depleted Monterey Formation A1-A2 storage reservoir exists prior to the commencement of CO₂ injection. Through


time, the injection pressure differential will shrink, until at the time of project abandonment when the reservoir pressure will be at the initial conditions of the reservoir. Due to high permeability, continuity of the reservoir and low injection pressure differential of the reservoir, pressure stabilization occurs within one year of injection cessation with the rate of change of pressure dropping below 10psi/year (0.027psi/day). Figure 1 shows the A1-A2 reservoir pressure increase during injection and pressure stabilization after injection from computational modeling.

Figure 1: Average Reservoir Pressure trend over the 15 year injection period and 100 years post injection.



Pressure at monitoring well 353A-7R will not decline post-injection (Figure 2). The low water saturation within the Monterey Formation A1-A2 storage reservoir results in greater than 98% of the CO₂ injectate remaining super-critical, minimizing the quantity of CO₂ dissolving in formation water through time.


Figure 2: Pressure at the 353A-7R monitoring well at start of injection, year two, four and post injection.



Predicted Position of the CO₂ Plume and Associated Pressure Front at Site Closure [40 CFR 146.93(a)(2)(ii)]

Figure 3 shows the predicted extent of the plume and pressure front at the end of the PISC timeframe, representing the maximum extent of the plume and pressure front. This map is based on the final AoR delineation modeling results submitted pursuant to 40 CFR 146.84.

Figure 3: Map of the predicted extent of the CO₂ plume at site closure. The pressure of the A1-A2 reservoir will be at or beneath the initial pressure at the time of discovery.



Post-Injection Monitoring Plan [40 CFR 146.93(b)(1)]

Monitoring during the post-injection phase will include pressure monitoring and fluid composition monitoring in the storage reservoir and reservoirs above the injection zone. Post-injection monitoring, as described in the following sections, will meet the requirements of 40 CFR 146.93(b)(1). The results of all post-injection phase testing and monitoring will be submitted annually, within 90 days of the anniversary date of final injection, as described under “Schedule for Submitting Post-Injection Monitoring Results,” below.

The Testing and Monitoring Plan describes the monitoring strategies within the injection zone, above the injection zone, and within the USDW-containing reservoir. In addition to monitoring the zones above the injection zone for stabilized pressure and absence of CO₂, the injection zone will be monitored for pressure stabilization as the best method to confirm confinement within the storage reservoir. If pressure in the reservoir trends lower post injection and is inconsistent when compared to computational modeling results, CTV will assess for potential leakage.

The Quality Assurance and Surveillance Plan (QASP) for all testing and monitoring activities during the injection and post injection phases is provided in the Appendix to the Testing and Monitoring Plan.

Surface, mineral, and pore space rights for the Monterey Formation A1-A2 reservoir are owned entirely by CTV where all activities will take place. As such, site access is guaranteed for the duration of the project and for post-injection monitoring.

Monitoring Above the Confining Zone

Table 1 presents the monitoring methods, locations, and frequencies for monitoring above the confining zone. Table 2 identifies the parameters to be monitored and the analytical methods CTV will employ.

The pressures of these reservoirs may be affected by regional water recharge, injection, or withdrawal. For the Tulare Formation, CTV will compare these results to other groundwater monitoring wells in the Elk Hills Oil Field.

Table 1. Monitoring of ground water quality and geochemical changes above the confining zone.

Target Formation	Monitoring Activity	Data Collection Location(s)	Device	Spatial Coverage or Depth	Frequency (Injection)
Tulare	Fluid Sampling	USDW Monitoring Well	Pump	940' - 960' MD/VD	Quarterly
	Pressure	USDW Monitoring Well	Pressure Gauge	940' - 960' MD/VD	Continuous
	Temperature	USDW Monitoring Well	Temperature Sensor	940' - 960' MD/VD	Continuous
	Temperature	327-7R-RD1 353A-7R 335X-7R	Fiberoptic cable (DTS)	849' MD/VD 961' MD/VD 854' MD/VD	Continuous
Etchegoin	Fluid Sampling	327-7R-RD1	Sampling Device	3782' - 3934' MD 3780' - 3932' VD	Quarterly
	Pressure	327-7R-RD1	Pressure Gauge	3782' - 3934' MD 3780' - 3932' VD	Continuous
	Temperature	327-7R-RD1	Temperature Sensor	3782' - 3934' MD 3780' - 3932' VD	Continuous
	Temperature	353A-7R 335X-7R	Fiberoptic cable (DTS)	4100' - 4220' MD/VD 3850' - 3990' MD/VD	Continuous

Table 2. Summary of analytical and field parameters for water samples.

Parameters	Analytical Methods
Cations (Al, Ba, Mn, As, Cd, Cr, Cu, Pb, Se, Zn, Tl)	ICP-MS EPA Method 6020
Cations (Ca, Fe, K, Mg, Na, Si)	ICP-AES EPA Method 6010B
Anions (Br, Cl, F, NO ₃ , SO ₄)	Ion Chromatography, EPA Method 300.0, Rev. 2.1, Part A (1993)
Dissolved CO ₂	Coulometric titration ASTM D513-11
δ ¹³ C	Isotope ratio mass spectrometry
Hydrogen Sulfide	ISBT 14.0 (GC/SCD)
Total Dissolved Solids	Gravimetry; Method 2540 C
Alkalinity	Method 2320B
pH (field)	EPA 150.1
Specific Conductance	APHA 2510
Temperature (field)	Thermocouple
Water Density (field)	Oscillating body method
Dissolved Methane	SM 6211 B or 6211 C

Table 3. Sampling and recording frequencies for continuous monitoring.

Parameter	Device(s)	Location	Min. Sampling Frequency	Min. Recording Frequency
During active injection	Pressure Gauge	USDW Monitoring Well	5 hours	5 hours
Post injection	Pressure Gauge	USDW Monitoring Well	12 hours	12 hours

Notes:

- Sampling frequency refers to how often the monitoring device obtains data from the well for a particular parameter. For example, a recording device might sample a pressure transducer monitoring injection pressure once every two seconds and save this value in memory.
- Recording frequency refers to how often the sampled information gets recorded to digital format (such as a computer hard drive). For example, the data from the injection pressure transducer might be recorded to a hard drive once every minute.

Carbon Dioxide Plume and Pressure Front Tracking [40 CFR 146.93(a)(2)(iii)]

CTV will employ direct and indirect methods to track the extent of the carbon dioxide plume and the associated increase in pressure.

Table 4 presents the direct and indirect methods that CTV will use to monitor the CO₂ plume, including the activities, locations, and frequencies. The parameters to be analyzed as part of fluid sampling in the Monterey Formation A1-A2 (and associated analytical methods) are presented in Table 5.

Table 6 presents the direct and indirect methods that CTV will use to monitor the pressure front, including the activities, locations, and frequencies CTV will employ.

Fluid sampling will be performed as described in B.1. of the QASP; sample handling and custody will be performed as described in B.3. of the QASP; and quality control will be ensured using the methods described in B.5. of the QASP.


Table 4. Post-injection phase plume monitoring.

Target Formation	Monitoring Activity	Monitoring Location(s)	Frequency	Depth (ft)
DIRECT PLUME MONITORING				
Monterey Formation A1-A2	Fluid Sampling	353A-7R and 335X-7R	Quarterly	353A-7R: 8703' MD 335X-7R: 8667' MD
INDIRECT PLUME MONITORING				
Monterey Formation A1-A2	Pulse Neutron Logging	353A-7R and 335X-7R	Every five years	353A-7R – 8,773'– 9,130' MD 335X-7R – 8,737'–9,030' MD

Table 5. Summary of analytical and field parameters for fluid sampling in the injection zone.

Parameters	Analytical Methods
Cations (Al, Ba, Mn, As, Cd, Cr, Cu, Pb, Se, Zn, Tl)	ICP-MS EPA Method 6020
Cations (Ca, Fe, K, Mg, Na, Si, Sb)	ICP-AES EPA Method 6010B
Anions (Br, Cl, F, NO ₃ , SO ₄)	Ion Chromatography, EPA Method 300.0, Rev. 2.1, Part A (1993)
Dissolved CO ₂	Coulometric titration ASTM D513-11
δ13C	Isotope ratio mass spectrometry
Hydrogen Sulfide	ISBT 14.0 (GC/SCD)
Oxygen, Argon, and Hydrogen	ISBT 4.0 (GC/DID) GC/TCD
Total Dissolved Solids	Gravimetry; Method 2540 C
Alkalinity	Method 2320B
pH (field)	EPA 150.1
Specific Conductance	APHA 2510
Temperature (field)	Thermocouple

Figure 5: Cross-section showing plume CO2 injectate plume 50 years post injection and well locations for post-injection monitoring.



Schedule for Submitting Post-Injection Monitoring Results [40 CFR 146.93(a)(2)(iv)]

All post-injection site care monitoring data and monitoring results collected using the methods described above will be submitted to EPA in annual reports submitted within 90 days following the anniversary date on which injection ceases. The reports will contain information and data generated during the reporting period; i.e. well-based monitoring data, sample analysis, and the results from updated site models.

Non-Endangerment Demonstration Criteria

Prior to authorization of site closure, CTV will submit a demonstration of non-endangerment of USDWs to the Director as per 40 CFR 143.93(b)(2) or (3).

CTV will provide a report to the Director that demonstrated USDW non-endangerment based on the evaluation of site monitoring data. The report will detail how the non-endangerment determination is based on site-specific conditions, supported with the computational model. All relevant monitoring data and interpretations will be provided.

Summary of Monitoring Data

A summary of the site monitoring data, pursuant to the Testing and Monitoring Plan and this PISC and Site Closure Plan, including data collected during the injection and PISC phases of the project. Data submission will be in a format acceptable to the Director and will include:

1. A narrative that explains the monitoring activities,
2. Dates of all monitoring events,

3. Changes to the monitoring program over time,
4. An explanation of all monitoring information that has existed at the site,
5. Explanation of how the monitoring data from injection and PISC has varied from the baseline data during site characterization, and
6. Summary of any emergencies that occurred during the injection and post-injection phases of the project. Included will be a description of how any issues have been resolved and that there is no endangerment to the USDW.

Evaluation of the CO₂ Plume and the AoR

Computational modeling results calibrated with monitoring data (e.g., pressure) will be used to support that the plume has stabilized and that the pressure change is negligible (less than 10 psi per year) and poses no risk for potential vertical migration. Computational modeling results calibrated with monitoring data from storage reservoir, USDW and above zone will be used to demonstrate:

1. the lack of CO₂ leakage over the project timeframe,
2. the accuracy of the model to predict and represent the storage reservoir, and
3. the computational model adequately defined the AoR.

Evaluation of Reservoir Pressure

Monitoring data will be reviewed to ensure that the CO₂ plume has stabilized post-injection and that the reservoir pressure change is negligible (less than 10 psi per year). This demonstration will be supported by the computational model that has been calibrated with the most recent monitoring data. The plume is trapped by structure and pinch-out of the reservoir sands. Plume migration is minimal, as such pressure stabilization will be used for non-endangerment assessment.

Evaluation of Potential Conduits for Fluid Movement

Wells that require corrective action will be reviewed and assessed prior to PISC and Site Closure, this includes monitoring wells, injection wells and other wells that penetrate within the AoR and the confining layer. Final demonstration will be made that natural and artificial conduits will not allow fluid migration from the storage reservoir.

Evaluation of Seismicity Monitoring

Demonstration will be made that the plume has stabilized and the pressure change is negligible (less than 10 psi per year), minimizing the risk for induced seismicity after site closure. Final review will be made with the seismicity monitoring to demonstrate seal integrity and that there is no further endangerment of to the USDW.

Site Closure Plan

CTV will conduct site closure activities to meet the requirements of 40 CFR 146.93(e), with notification to the permitting agencies at least 120 days prior to its intent to close the site. Upon approval of the permitting agencies, CTV will plug the injection and monitoring wells, restore the site, and submit a site closure plan to the EPA.

A site closure report will be prepared and submitted within 90 days following site closure supported by the following:

1. Verification of injector and monitoring well plugging,
2. Notifications to state and local authorities as per 40 CFR 146.93 (f)(2),
3. Composition and volume of the injected CO₂, and
4. Post-injection monitoring records

CTV will record a notation to the property's deed that will indicate:

1. The property was used for CO₂ sequestration, the period of injection and the volume of CO₂ injected,
2. The formation that the fluid was injected, and
3. The name of the local agency to which a plat of survey with injection well locations was submitted.